

Zenit W600

Zenit Series



#CLZW600

Equipped with a total of forty 15 W RGBW LEDs for a massive 21,000 Im output, the Cameo ZENIT® W600 is a powerful IP65 rated wash light for demanding outdoor applications. In addition to RDM and standard DMX capability it boasts a built-in 2.4 GHz W-DMXTM transceiver by Wireless Solution Sweden AB for convenient wireless control. The fixture also provides a rich variety of stunning automated programs for standalone or wireless master-and-slave operation. For maximum versatility, the ZENIT® W600 sports Cameo's innovative SnapMag® technology. It allows you to add filter frames in less than a second without the need for tools or dismantling. Magnetic SnapMag® frames with precision light shaping diffusers providing a choice of 25°, 45°, 100° or elliptical 60° x 10° beam angles and a 4-way barn door are available as dedicated accessories.

Technical Informations

Product type

LED Outdoor Wash Light

Type

ZENIT

Colour spectrum

RGBW



Number of LEDs	40
LED Type	15W
Average LED lifetime	50000 hrs
Refresh rate	Adjustable: 800Hz, 1200Hz, 2000Hz, 3600Hz, 12000Hz 25000 Hz
Dispersion	18° Beam, 35° Field (without diffusor) °
Lens	PE and tempered glass
DMX Input	5-pin IP65
DMX Output	5-pin IP65
DMX Mode	10-channel, 15-channel, 2-channel, 3-channel, 4-channel, 8-1 Channel, 8-2 Channel
DMX Function	



Auto programs, colour macro, CTC (Colour Temperature Correction), Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, RGBW, RGBW Fine, strobe

Standalone Modes	Auto programs, colour macro, Master / Slave mode, Settings, Static, system info, Tunable White, User Colours
Controls	Enter, Mode, Value Down, Value Up
Indicators	OLED Display
Operating voltage	100 V AC – 240 V AC, 50 – 60 Hz
Power consumption	565 W
Power Factor	0,99 FP (120 V) / 0,96 FP (230 V)
Power connector	IP65
Power supply connection	IP65
Housing material	Aluminium



	Cabinet colour	
		Black
	Protection class IP	IP65
	Cooling	IP65 temperature-controlled fans
	Luminous flux	21000 lm
	Efficiency	37,2 lm/W
	Operating Temperature	-15 – 45 °C
	Accessories (included)	2 x omega mounting
	Other features	ETL certified
Dimensions	Width	463 mm
	Length	291 mm



Height	161 mm
Weight	13 kg