Zenit W600

Zenit Series



#CLZW600

Equipped with a total of forty 15 W RGBW LEDs for a massive 21,000 lm output, the Cameo ZENIT® W600 is a powerful IP65 rated wash light for demanding outdoor applications. In addition to RDM and standard DMX capability it boasts a built-in 2.4 GHz W-DMX™ transceiver by Wireless Solution Sweden AB for convenient wireless control. The fixture also provides a rich variety of stunning automated programs for standalone or wireless master-and-slave operation. For maximum versatility, the ZENIT® W600 sports Cameo's innovative SnapMag® technology. It allows you to add filter frames in less than a second without the need for tools or dismantling. Magnetic SnapMag® frames with precision light shaping diffusers providing a choice of 25°, 45°, 100° or elliptical 60° x 10° beam angles and a 4-way barn door are available as dedicated accessories.

Technical Informations

Product type

LED Outdoor Wash Light

Type

ZENIT

Colour spectrum

RGBW

Number of LEDs	40
LED Type	15W
Average LED lifetime	50000 hrs
Refresh rate	Adjustable: 800Hz, 1200Hz, 2000Hz, 3600Hz, 12000Hz, 25000 Hz
Dispersion	18° Beam, 35° Field (without diffusor) °
Lens	PE and tempered glass
DMX Input	5-pin IP65
DMX Output	5-pin IP65
DMX Mode	10-channel, 15-channel, 2-channel, 3-channel, 4-channel, 8-1 Channel, 8-2 Channel
DMX Function	

	Auto programs, colour macro, CTC (Colour Temperature Correction), Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, RGBW, RGBW Fine, strobe
Standalone Modes	
	Auto programs, colour macro, Master / Slave mode, Settings, Static, system info, Tunable White, User Colours
Controls	
	Enter, Mode, Value Down, Value Up
Indicators	
	OLED Display
Operating voltage	
	100 V AC – 240 V AC, 50 – 60 Hz
Power consumption	
	565 W
Power Factor	
	0,99 FP (120 V) / 0,96 FP (230 V)
Power connector	
	IP65
Power supply connection	
	IP65
Housing material	
	Aluminium

Cabinet colour	Black
Protection class IP	IP65
Cooling	IP65 temperature-controlled fans
Luminous flux	21000 lm
Efficiency	37,2 lm/W
Operating Temperature	-15 – 45 °C
Accessories (included)	2 x omega mounting
Other features	ETL certified

Dimensions

Width	463 mm
Length	291 mm

Height	
	161 mm
Weight	
	13 kg