



Zenit W300

Zenit Series



#CLZW300

Equipped with a total of twenty-one 15 W RGBW LEDs for a huge 10,000 lm output, the Cameo ZENIT® W300 is a powerful IP65 rated wash light for demanding outdoor applications. In addition to RDM and standard DMX capability it boasts a built-in 2.4 GHz W-DMX™ transceiver by Wireless Solution Sweden AB for convenient wireless control. The fixture also provides a rich variety of stunning automated programs for standalone or wireless master-and-slave operation. For maximum versatility, the ZENIT® W300 sports Cameo's innovative SnapMag® technology. It allows you to add filter frames in less than a second without the need for tools or dismantling. Magnetic SnapMag® frames with precision light shaping diffusers and a 4-way barn door are available as dedicated accessories.

Technical Informations

Product Type

LED Outdoor Wash Light

Type

ZENIT

Colour spectrum

RGBW

**Number of LEDs**

21

LED type

15 W

Average LED lifetime

50000 hrs

Refresh rate

Adjustable: 800, 1200, 2000, 3600, 12000, 25000 Hz

Dispersion

21 ° Beam, 40 ° Field (without Diffusor) °

Lens

PE and tempered glass

DMX input

5-pin IP65

DMX output

5-pin IP65

DMX mode10-channel, 15-channel, 2-channel, 3-channel,
4-channel, 8-1 Channel, 8-2 Channel**DMX Functions**

Auto programs, colour macro, CTC (Colour



Temperature Correction), Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, RGBW, RGBW Fine, strobe

Standalone Modes

Auto programs, colour macro, Device Settings, Master / Slave mode, Static, system info, Tunable White, User Colours

Controls

Enter, Mode, Value Down, Value Up

Indicators

OLED Display

Operating voltage

100 V AC – 240 V AC, 50 – 60 Hz

Power consumption

300 W

Power Factor

0.99 PF (120V) / 0.96 PF (230V)

Power Connector

IP65

Power supply connection

IP65

Housing material

Aluminium

**Cabinet colour**

Black

Protection class IP

IP65

Cooling

IP65 temperature-controlled fans

Luminous flux

10661 lm

Efficiency

35.3 lm/W

**Operating
Temperature**

-15 – 45 °C

Other features

ETL certified

Dimensions**Width**

377 mm

Length

256 mm

Height

140 mm



Weight

8 kg
