

Zenit W300

Zenit Series



#CLZW300

Equipped with a total of twenty-one 15 W RGBW LEDs for a huge 10,000 lm output, the Cameo ZENIT® W300 is a powerful IP65 rated wash light for demanding outdoor applications. In addition to RDM and standard DMX capability it boasts a built-in 2.4 GHz W-DMX™ transceiver by Wireless Solution Sweden AB for convenient wireless control. The fixture also provides a rich variety of stunning automated programs for standalone or wireless master-and-slave operation. For maximum versatility, the ZENIT® W300 sports Cameo's innovative SnapMag® technology. It allows you to add filter frames in less than a second without the need for tools or dismantling. Magnetic SnapMag® frames with precision light shaping diffusers and a 4-way barn door are available as dedicated accessories.

Technical Informations

Product Type

LED Outdoor Wash Light

Туре

ZENIT

Colour spectrum

RGBW



Number of LEDs	21
LED type	15 W
Average LED lifetime	50000 hrs
Refresh rate	Adjustable: 800, 1200, 2000, 3600, 12000, 25000 Hz
Dispersion	21 ° Beam, 40 ° Field (without Diffusor) °
Lens	PE and tempered glass
DMX input	5-pin IP65
DMX output	5-pin IP65
DMX mode	10-channel, 15-channel, 2-channel, 3-channel, 4-channel, 8-1 Channel, 8-2 Channel
DMX Functions	Auto programs, colour macro, CTC (Colour



Temperature Correction), Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, RGBW, RGBW Fine,

Standalone Modes	Auto programs, colour macro, Device Settings, Master / Slave mode, Static, system info, Tunable White, User Colours
Controls	Enter, Mode, Value Down, Value Up
Indicators	OLED Display
Operating voltage	100 V AC – 240 V AC, 50 – 60 Hz
Power consumption	300 W
Power Factor	0.99 PF (120V) / 0.96 PF (230V)
Power Connector	IP65
Power supply connection	IP65
Housing material	Aluminium



	Cabinet colour		
		Black	
	Protection class IP	IP65	
	Cooling	IP65 temperature-controlled fans	
	Luminous flux	10661 lm	
	Efficiency	35.3 lm/W	
Temperati	Operating Temperature	-15 – 45 °C	
	Other features Width	ETL certified	
		377 mm	
	Length	256 mm	
	Height	140 mm	



W	<i>l</i> ei	'n	ht	
		ч	111	

8 kg