



# Opus S5

Opus Series



## #CLOS5

Illuminating stages with brilliant, lively colours, the Cameo OPUS® S5 is a compact super bright spot moving head with a powerful 380 W white LED engine, CMY mixing system and linear CTO correction. It is highly effective in venues of all sizes thanks to its wide zoom range. An additional colour wheel with 7 dichroic filters enables instant colour changes and split colour projection. The fixture has an enormous 17,500 lm output, huge illuminance of 39,000 lux at a distance of 5 meters and rapid 540° pan and 270° tilt movement. Permitting extensive beam control, the highly efficient optics feature an extra wide zoom range from 6° to 46° and stepless iris. A continuously variable frost filter provides soft, wash-like diffusion. The OPUS® S5 offers flexible control options via DMX, RDM, Art-Net, sACN or the built-in W-DMX™ transceiver. It has a rugged ABS and metal housing with Neutrik® DMX and powerCON TRUE1 connectors and super efficient heat pipe cooling system with temperature controlled fans to ensure optimal cooling. A battery-powered touchscreen display with 6 additional touch buttons permits convenient offline configuration and two modes of menu navigation. The luminaire comes with two omega brackets and power cord.

## Technical Informations

### Product type

LED Moving Lights

### Type

Profiles

### Colour spectrum



Cold white

**Number of LEDs**

1

**Color temperature**

6700 K

**LED type**

380 W

**Dispersion**

6 – 48 °

**Effects**

4-Blade – 2 axis – Framing, Focus, Framing rotation 90°, Heavy Frost, Iris, Zoom

**Colour mixing function**

CMY + CTO

**LED PWM Frequency**

650 Hz, 1530 Hz, 3600 Hz, 12000 Hz, 25000 Hz (adjustable)

**Color wheel**

1

**Number of gobos**

15 + open (8 fixed + 7 rotating)

**DMX input**

XLR 3-pin male, XLR 5-pin male

**DMX output**

XLR 3-pin female, XLR 5-pin female

**DMX mode**

27-channel, 33-channel

**DMX Functions**

Animation Wheel, Auto Movement, Colour wheel, CTO, CTO Fine, Cyan, Cyan Fine, Device Settings, Dimmer, Dimmer Fine, Focus, Focus Fine, Frost, Gobo wheel, Gobo Wheel 1, Gobo Wheel 2, Iris, Magenta, Magenta Fine, PAN, PAN FINE, Prism, Rotation Fine, Rotation Gobo Wheel 1, Rotation Prism, Set Dimmer Curve, strobe, TILT, TILT FINE, Yellow, Yellow Fine, Zoom, Zoom Fine

**PAN movement**

540°

**TILT movement**

270°

**High Speed Strobe**

> 20 Hz

**Standalone modes**

Master/Slave Mode, Static Mode

**Control**

ArtNet, DMX, Master/Slave Signal, RDM, sACN, Wireless DMX

**Controls**

Down, Enter, Left, Mode, Right, Up

**Indicators**

Graphic Display

**Operating voltage**

100 V AC – 240 V AC, 50 – 60 Hz, Neutrik True 1 IN / OUT

**Power consumption**

650 W

**Power connector**

Neutrik powerCON TRUE1 TOP

**Housing material**

ABS plastic, Metal

**Cabinet colour**

Black

**Protection class IP**

IP20

**Cooling**

Silent, temperature controlled fan

**Luminous flux**



17500 lm

**Maximum Ambient Temperature**

-10 – 45 °C

**Accessories (included)**

2 x omega mounting, Power cord, Power Cord with Neutrik powerCON TRUE1 Connector, User's manual

**Dimensions**

**Width**

400 mm

**Height**

630 mm

**Depth**

250 mm

**Weight**

24 kg