



# Drop B1

Drop Series



#CLDROPB1

Flexibility meets design! Professionals and rental firms are better prepared with this battery-powered PAR! Whether they're standing, hanging or mounted in some other way, our DROP series uplights always look good. This is thanks to their intelligently attached bracket with no visible screws. The innovative bracket is screwed onto the uplight from below and not from the side as is standard. When unmounted, the lamp boasts a very clean, simple exterior. Mounting options are flexible, either on the bracket or standing on rubber feet. When positioned upright and standing (without the mounted bracket), a built-in adjustment screw is available for tilt manipulation. This version also has a magnetic mount. Rated with protection class IP65, this uplight is also suitable for outdoor use. The LG Chemicals rechargeable lithium-ion battery ensures reliable operation.

## Technical Informations

### Product type

Battery powered LED outdoor lighting

### Type

Outdoor PAR, PAR

### Colour spectrum

RGBWA + UV

**Number of LEDs**

1

**LED type**

15 W

**Dispersion**

9 °, Filter 1: 11 °, Filter 2: 27 °

**DMX mode**

2 x 13-channel, 2-channel, 20-channel, 3-channel, 4-channel, 6-channel, 7-channel

**DMX functions**

CCT, colour change, colour fade, colour macro, Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, DMX Delay, RGBWA + UV Fine, strobe

**Standalone modes**

Auto programs, colour macro, Colour Mix, strobe, Tunable White, User Colours

**Control**

W-DMX

**Controls**

Down, Enter, Mode, Up

**Indicators**

OLED Display



<b>Operating voltage</b>	100 V AC – 240 V AC, 50 – 60 Hz
<b>Power consumption</b>	35 W
<b>Housing material</b>	Metal
<b>Cabinet colour</b>	Black
<b>Protection class IP</b>	IP65
<b>Relative Humidity</b>	< 85 %, not condensing
<b>Cooling</b>	Convection
<b>Illuminance</b>	6800 lx @ 1 m, 756 lx @ 3 m
<b>Luminous flux</b>	320 lm
<b>Maximum Ambient Temperature</b>	0 – 40 °C

**Certificates**

CE, ETL, FCC, RoHS

**Accessories  
(included)**

1 x Hemispherical filter, 1 x Mounting bracket, 2 x filter,  
IR Remote Control

**Dimensions****Width**

163.5 mm

**Height**

91 mm

**Depth**

112.5 mm

**Weight**

1 kg