Drop B4

Drop Series



#CLDROPB4

Flexibility meets design! Professionals and rental firms are better prepared with this battery-powered PAR! Whether they're standing, hanging or mounted in some other way, our DROP series uplights always look good. This is thanks to their intelligently attached bracket with no visible screws. The innovative bracket is screwed onto the uplight from below and not from the side as is standard. When unmounted, the lamp boasts a very clean, simple exterior. Mounting options are flexible, either on the bracket or standing on rubber feet. When positioned upright and standing (without the mounted bracket), a built-in adjustment screw is available for tilt manipulation. Rated with protection class IP65, this uplight is also suitable for outdoor use. The long-life battery also ensures reliable operation.

Technical Informations

Product type

Battery powered LED outdoor lighting

Type

Battery-powered, Outdoor PAR, PAR

Colour spectrum

RGBWA + UV

Number of LEDs

4

Dispersion

(Filter 1) 32 °, (Filter 2) 45 °, 22 °

DMX mode

2 x 13-channel, 20-channel, 3-channel, 4-channel, 6-channel, 7-channel

DMX Functions

CCT, colour change, colour fade, colour macro, Dimmer, Dimmer Curve, Dimmer Fine, Dimmer Response, DMX Delay, RGBWA + UV, strobe

Standalone modes

Auto programs, colour macro, Colour Mix, strobe, Tunable White, User Colours

Control

IR Remote Control, W-DMX

Controls

Down, Enter, Mode, Up

Indicators

OLED Display

Operating voltage

100 V AC – 240 V AC, 50 – 60 Hz

Power consumption	75 W
Power connector	External Power Supply
Housing material	Metal
Cabinet colour	Black
Protection class IP	IP65
Cooling	Convection
Illuminance	6750 lx @ 1 m
Luminous flux	1400 lm
Maximum Ambient Temperature	0 – 40 °C
Relative Humidity	< 85 %, not condensing

	Certifications	CE, ETL, FCC, RoHS
	Accessories (included)	1 x Mounting bracket, 2 x filter, IR Remote Control
Dimensions	**Width**	240 mm
	Height	142,5 mm
	Depth	162,5 mm
	Weight	3,1 kg