



# Drop P4

Drop Series



#CLDROPP4

Flexibility meets design! Professionals and rental firms are better prepared with this uplight! Whether they're standing, hanging or mounted in some other way, our DROP series uplights always look good. This is thanks to their intelligently attached bracket with no visible screws. The innovative bracket is screwed onto the uplight from below and not from the side as is standard. This means that when unmounted, the lamp boasts a very clean, simple exterior. Mounting options are flexible, either on the bracket or standing on rubber feet. When positioned upright and standing (without the mounted bracket), a built-in adjustment screw is available for tilt manipulation. Rated with protection class IP65, this uplight is also suitable for outdoor use.

## Technical Informations

### Product type

LED Wash Light

### Type

Outdoor PAR

### Colour spectrum

RGBWA + UV

**Number of LEDs**

4

**LED type**

15 W

**Dispersion**

22 °, 32 °, 40 °

**DMX input**

XLR 3-pin female

**DMX output**

XLR 3-Pol male IP65

**DMX Functions**

Colour change, colour fade, colour macro, Colour temperature correction, Dimmer, Dimmer Curve, Dimmer Fine, Dimmer response, LED PWM Frequency, RGBWA + UV, RGBWA + UV Fine, strobe

**Standalone modes**

Auto programs, colour macro, Colour Mix, Master / Slave mode, strobe, Tunable White, User Colours

**Control**

DMX, RDM

**Controls**

Down, Enter, Mode, Up

**Indicators**

OLED Display

**Power consumption**

45 W

**Power connector**

Neutrik PowerCON TRUE1 IN / OUT

**Housing material**

ABS, Metal

**Cabinet colour**

Black

**IP class**

IP65

**Cooling**

Silent, temperature controlled fan

**Luminous flux**

1400 lm

**Maximum Ambient  
Temperature**

0 – 40 °C

**Relative Humidity**

&lt; 85 %, not condensing

**Certification**

E, ETL, FCC, RoHS

**Accessories  
(included)**

1 x Mounting bracket, 2 x filter, Neutrik PowerCon

**Dimensions****Width**

186 mm

**Height**

170 mm

**Depth**

170 mm

**Weight**

3,1 kg