

Drop P4

Drop Series



#CLDROPP4

Flexibility meets design! Professionals and rental firms are better prepared with this uplight! Whether they're standing, hanging or mounted in some other way, our DROP series uplights always look good. This is thanks to their intelligently attached bracket with no visible screws. The innovative bracket is screwed onto the uplight from below and not from the side as is standard. This means that when unmounted, the lamp boasts a very clean, simple exterior. Mounting options are flexible, either on the bracket or standing on rubber feet. When positioned upright and standing (without the mounted bracket), a built-in adjustment screw is available for tilt manipulation. Rated with protection class IP65, this uplight is also suitable for outdoor use.

Technical Informations

Product type

LED Wash Light

Туре

Outdoor PAR

Colour spectrum

RGBWA + UV



Number of LEDs	4
LED type	15 W
Dispersion	22°, 32°, 40°
DMX input	XLR 3-pin female
DMX output	XLR 3-Pol male IP65
DMX Functions	Colour change, colour fade, colour macro, Colour temperature correction, Dimmer, Dimmer Curve, Dimmer Fine, Dimmer response, LED PWM Frequency, RGBWA + UV, RGBWA + UV Fine, strobe
Standalone modes	Auto programs, colour macro, Colour Mix, Master / Slave mode, strobe, Tunable White, User Colours
Control	DMX, RDM
Controls	Down, Enter, Mode, Up



Indicators	OLED Display
Power consumption	45 W
Power connector	Neutrik PowerCON TRUE1 IN / OUT
Housing material	ABS, Metal
Cabinet colour	Black
IP class	IP65
Cooling	Silent, temperature controlled fan
Luminous flux	1400 lm
Maximum Ambient Temperature	0 – 40 °C
Relative Humidity	< 85 %, not condensing



	Certification	E, ETL, FCC, RoHS
	Accessories (included)	1 x Mounting bracket, 2 x filter, Neutrik PowerCon
Dimensions	Width	186 mm
	Height	170 mm
	Depth	170 mm
	Weight	3,1 kg