



CD-112A

Theatrical



#CD112A

Built to withstand the daily hazards of touring, the CD-112A Theatrical Electrical Distribution is made to minimize the technical back stage area by taking only five rackmount units. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for audio and stage power applications. It offers 6 separate TL4 30A 120/240V (L14-30) connectors over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

6x L14-30 Receptacles



	Breakers	6x 30A 120/240V
Features	Single/Three Phase Switch	Yes, easy access from top of enclosure
	Phase Presence Indicators	1x neon light per input phase
	Voltage Metering Jacks	1x fused tip jack per input phase + 1x unfused tip jack on Neutral
	Enclosure Construction	Robust steel housing
Dimensions	Height	222.25 mm (8.75?) – 5RU
	Depth	516.00 mm (20.32?)
	Width	482.60 mm (19.00?)

Certifications



DESIGNED & MANUFACTURED
IN CANADA 