



CD-112B

Theatrixx



#CD112B

Built to withstand the daily hazards of touring, the CD-112B Theatrixx Electrical Distribution is made to minimize the technical back stage area by taking only five rackmount units. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for lighting and stage power applications. It offers 4 separate TL5 30A 120/208V 3 phases (L21-30) connectors over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

4x L21-30 Receptacles



Breakers

4x 30A 120/208V

Features

Single/Three Phase Switch

Yes, easy access from top of enclosure

Phase Presence Indicators

1x neon light per input phase

Voltage Metering Jacks

1x fused tip jack per input phase + 1 unfused tip jack on Neutral

Enclosure Construction

Robust steel housing

Dimensions

Height

222.25 mm (8.75?) – 5RU

Depth

516.00 mm (20.32?)

Width

482.60 mm (19.00?)

Certifications



DESIGNED & MANUFACTURED
IN CANADA