
SD-112A

Theatrixx



#SD112A

Built to withstand the daily hazards of touring, the SD-112A Theatrixx electrical Distribution is made to minimize the technical back stage area by taking only 6 rackmount units. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for audio, lighting and stage power applications. It offers 4 separate P&S 30A 120/208V 3 phases (C5) connectors over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

4x PS530R9 (C5) Receptacles

Features

Breakers	4x 30A 120/208V Circuits
Phase Presence Indicators	1x neon light per input phase
Voltage Metering Jacks	1x fused tip jack per input phase + 1x unfused tip jack on Neutral
Enclosure construction	Robust steel housing

Dimensions

Height	266.70 mm (10.50?) – 6RU
Depth	538.00 mm (21.18?)
Width	482.60 mm (19.00?)

Certifications

DESIGNED & MANUFACTURED IN CANADA