



# SD-124A

Theatrical



## #SD124A

Built to withstand the daily hazards of touring, this SD-124A Theatrical Electrical Distribution features an impressive amount of options in such a small format of only 6 rack units. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for audio and stage power applications. It offers 4 separate TL5 30A 120/208V (L21-30) connectors and 6 split 20A Edison Duplex (5-20) over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks.

### Input

#### Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

#### Breaker

100A 120/208V 3 phases Main Breaker

### Outputs

#### Connectors

4x L21-30 Receptacles  
6x 5-20 Duplex



	<b>Breakers</b>	4x 30A 120/208V Circuits 12x 20A 120V Circuits
<b>Features</b>	<b>Digital Metering</b>	Yes, integrated multifunction voltmeter/ammeter/wattmeter
	<b>Phase Presence Indicators</b>	1x neon light per input phase
	<b>Voltage Metering Jacks</b>	1x fused tip jack per input phase + 1x unfused tip jack on Neutral
	<b>Enclosure construction</b>	Robust steel housing
<b>Dimensions</b>	<b>Height</b>	266.70 mm (10.50?) – 6RU
	<b>Depth</b>	516.00 mm (20.32?)
	<b>Width</b>	482.60 mm (19.00?)

---

## Certifications



DESIGNED & MANUFACTURED  
IN CANADA 