SD-128A

Theatrixx



#SD128A

Built to withstand the daily hazards of touring, this SD-128B Theatrixx Electrical Distribution features an impressive amount of options in such a small format of only 6 rack units.. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for lighting and stage power applications. It offers 24 separate 120V circuits on 4x Socapex and 2 split 20A Edison Duplex (5-20) over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

4x Socapex 19 pins (120V)
2x 5-20 Duplex

Breakers	24x 20A 120V Circuits 4x 20A 120V Circuits

Features

Digital Metering	Yes, integrated multifunction voltmeter/ammeter/wattmeter
Single/Three Phase Switch	Yes, easy access from top of enclosure
Phase Presence Indicators	1x neon light per input phase
Voltage Metering Jacks	1x fused tip jack per input phase + 1x unfused tip jack on Neutral
Enclosure construction	Robust steel housing

Dimensions

Height	266.70 mm (10.50?) – 6RU
Depth	516.00 mm (20.32?)
Width	482.60 mm (19.00?)

Certifications

DESIGNED & MANUFACTURED
IN CANADA