VD-126X

Theatrixx



#VD126X

Built to withstand the daily hazards of touring, this VD-126X Theatrixx Electrical Distribution features an impressive amount of options for such a small format. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is specifically designed to be used with xVision Video panels. It offers 12 separate 208V** circuits on 2 X Socapex connectors and 2 X 20A Edison Duplex (5-20) over a 100A 3 phases Main Breaker. Each Circuit 5 & 6 of the Socapex is doubled on a XVT3 Female connector. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

2x Socapex 19 pins
4x XVT3 Female
2x 5-20 Duplex

Features

Breakers	12x 20A 208V Circuits** 2x 20A 120V Circuits
Digital Metering	Yes, integrated multifunction voltmeter/ammeter/wattmeter
Single/Three Phase Switch	Yes, easy access from top of enclosure
Phase Presence Indicators	1x neon light per Input phase
Voltage Metering Jacks	1x fused tip jack per Input phase + 1x unfused tip jack on Neutral
Enclosure construction	Robust steel housing

Dimensions

Height	266.70 mm (10.5?) – 6RU
Depth	516.00 mm (20.32?)
Width	482.60 mm (19.00?)

***Customer must specify 208V pinout configuration when ordered*

Certifications

DESIGNED & MANUFACTURED IN CANADA