
VD-251X

Theatrixx



#VD251X

Built to withstand the daily hazards of touring, this VD-251X Theatrixx Electrical Distribution features an impressive amount of options for such a small format. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. It also features a handle protection over the Main Breaker switch. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is specifically designed to be used with xVision Video panels. It offers 24 separate 208V** circuits on 4 X Socapex connectors and 3 X 20A Edison Duplex (5-20) over a 200A 3 phases Main Breaker. Each Circuit 5 & 6 of the Socapex is doubled on a XVT3 Female connector. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

200A 120/208V 3 phases Main Breaker

Outputs

Connectors

4x Socapex 19 pins
8x XVT3 Female

		3x 5-20 Duplex
	Breakers	
		24x 20A 208V Circuits** 3x 20A 120V Circuits
Features	**Digital Metering**	
		Yes, integrated multifunction voltmeter/ammeter/wattmeter
	Single/Three Phase Switch	
		Yes, easy access from top of enclosure
	Phase Presence Indicators	
		1x neon light per Input phase
	Voltage Metering Jacks	
		1x fused tip jack per Input phase + 1x unfused tip jack on Neutral
	Enclosure construction	
		Robust steel housing
Dimensions	**Height**	
		400.05 mm (15.75?) – 9RU
	Depth	
		516.00 mm (20.32?)
	Width	
		482.60 mm (19.00?)

***Customer must specify 208V pinout configuration when ordered*

Certifications

DESIGNED & MANUFACTURED IN CANADA