
VD-476X

Theatrixx



#VD476X

Built to withstand the daily hazards of touring, this VD-476X Theatrixx Electrical Distribution features an impressive amount of options for such a small format. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. It also features handle protection over the 2 Main Breaker switches. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is specifically designed to be used with xVision Video panels. It offers 36 separate 208V** circuits on 6 X Socapex connectors and 4 X 20A Edison Duplex (5-20) over 2 X 200A 3 phases Main Breaker (Total 400A). Each Circuit 5 & 6 of the Socapex is doubled on a XVT3 Female connector. Panel mount terminals and neon indicators allow quick and easy voltage checks.

Input

Connector

CAM In/Thru – Straight or Ground/Neutral Reversed

Breaker

2x 200A 120/208V 3 phases Main Breaker (400A Total)

Outputs

Connectors

6x Socapex 19 pins
12x XVT3 Female
4x 5-20 Duplex

Features

Breakers	36x 20A 208V Circuits** 4x 20A 120V Circuits
Digital Metering	Yes, integrated multifunction voltmeter/ammeter/wattmeter
Single/Three Phase Switch	Yes, easy access from top of enclosure
Phase Presence Indicators	1x neon light per Input phase
Voltage Metering Jacks	1x fused tip jack per Input phase + 1x unfused tip jack on Neutral
Enclosure construction	Robust steel housing

Dimensions

Height	622.30 mm (24.50?) – 14RU
Depth	516.00 mm (20.32?)
Width	482.60 mm (19.00?)

***Customer must specify 208V pinout configuration when ordered*

Certifications

DESIGNED & MANUFACTURED IN CANADA