



WD-124A

Theatrical



#WD124A

Built to withstand the daily hazards of touring, this WD-124A Theatrical Electrical Distribution features an impressive amount of options for such a small format. The front panel is cut from a robust 0.080" aluminum sheet and is fixed to a robust steel enclosure which is then inserted in a Nanuk type 950 transport case. This type of power distribution is designed for audio and stage power applications. It offers 6 separate TL4 30A 120/240V (L14-30) connectors and 4 split 20A Edison Duplex (5-20) over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input

Connector

CAM In – Straight or Ground/Neutral Reversed

Breaker

100A 120/208V 3 phases Main Breaker

Outputs

Connectors

6x L14-30 Receptacles
4x 5-20 Duplex



Features	Breakers	6x 30A 120/240V Circuits 8x 20A 120V Circuits
	Digital Metering	Yes, integrated multifunction voltmeter/ammeter/wattmeter
	Single/Three Phase Switch	Yes, easy access from top of enclosure
	Phase Presence Indicators	1x neon light per Input phase
	Voltage Metering Jacks	No
	Enclosure construction	Type 950 Nanuk Transport Case
Dimensions	Height	297,18mm (11.7")
	Depth	464,82mm (18.3?)
	Width	579,12mm (22.8?)



Certifications



DESIGNED & MANUFACTURED
IN CANADA 