WD-128B

Theatrixx

 (\mathbf{X})



#WD128B

Built to withstand the daily hazards of touring, this WD-128B Theatrixx Electrical Distribution features an impressive amount of options for such a small format. The front panel is cut from a robust 0.080" aluminum sheet and is fixed to a robust steel enclosure which is then inserted in a Nanuk type 950 transport case. This type of power distribution is designed for lighting and stage power applications. It offers 12 separate 208V** circuits on doubled Socapex (120V and 208V) and 2 split 20A Edison Duplex (5-20) over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks. It also features a 1 to 3 phases selection located on top under an easy access trap door.

Input	Connector	CAM In – Straight or Ground/Neutral Reversed
	Breaker	100A 120/208V 3 phases Main Breaker
Outputs	Connectors	2x Socapex 19 pins (208V) 2x Socapex 19 pins (120V) 4x 5-20 Duplex

	Breakers	12x 20A 208V Circuits** 8x 20A 120V Circuits
Features	Digital Metering	Yes, integrated multifunction voltmeter/ammeter/wattmeter
	Single/Three Phase Switch	Yes, easy access from top of enclosure
	Phase Presence Indicators	1x neon light perInput phase
	Voltage Metering Jacks	No
	Enclosure construction	Type 950 Nanuk Transport Case
Dimensions	Height	297,18mm (11.7")
	Depth	464,82mm (18.3?)

Width



**Customer must specify 208V pinout configuration when ordered

Certifications



DESIGNED & MANUFACTURED IN CANADA 👾