



XD - 86" UHD - 410nits

Vestel



#XD86B-4F

Display Control over RS232 and LAN Our platform allows users to control their displays, using a large range of commands through either a Local Area Network or direct RS232 Serial connection. **Wireless Display** Using either Microsoft Wireless Display Adaptor or Android Screen Sharing functions on Windows and Android devices, you can mirror screen to the display using embedded wireless display capabilities without using any external devices or cables.

Specifications	-	3840x2160 (UHD) Resolution
	-	400 cd/m2 Brightness
	-	16/7 Operation
	-	Ultra Narrow Bezel

Panel

Screen Size

86"

**Backlight Type**

Edge-Type LED

Brightness (typical)410 cd/m²**Native Resolution**

3840 x 2160 (16:9) – UHD

**Contrast Ratio
(typical)**

1200:1

**Dynamic Contrast
Ratio**

40000:1

**Panel Life Time
(Min.)**

50000 Hrs

**Response Time
(typical)**

8 ms

Active Area (H x V)

1895 x 1066 mm

Viewing Angle

178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10

Color Value

1.07 B (10-bit)



Screen Treatment

2H

Haze Level

3%

Refresh Rate

60 Hz

Orientation

Horizontal

Operation Hours

16/7

Area of Usage

Indoor

Monitor Connectivity

RGB Input

VGA(DE-15F)

RGB Output

N/A

Video Input

4xHDMI2.0, DP1.2a, 2xUSB2.0, USB2.0(Internal)

Video Output

HDMI2.0, DP1.2a

**Audio Input**

Line In L/R

Audio Output

Headphone, Optic SPDIF

External Control

RS232(DE-9F), Ethernet(RJ45), Service(RJ12)

External Sensor

RJ12

Environmental**Operating Temperature**

0-40°C

Operating Humidity

10-90%

Power Consumption**Typical**

300 W

Deep Standby

?0.5 W

Power**Power Supply**

110 VAC – 240 VAC – 50/60 Hz

Accessory**Standard**

QSG, IB, Power Cord, Remote Control, RC Battery,



Mounting Kit, Extension Brackets, IR Extender Cable

Mechanical

Product Dimensions (WxDxH)

1928 x 80 x 1099 mm

Package Dimensions (WxDxH)

2163 x 380 x 1405 mm

Product Weight

61.95 kg

Package Weight

83.8 kg

Vesa Mounting

600 x 400 mm – M6

Bezel Width

B/T/L/R:12 mm

Features

Main Features

Open Content Management Support, Scheduler, USB-Autoplay, Auto- Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, remote control via LAN, Real Time Clock

Mechanical Features

Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder



Optional Features

OPS Compliance, IR Overlay Touch Compliance

Speaker

2 x 12 W

Certification

Safety

yes

EMC

yes

CE

yes