



Drop P4

Drop Series



#CLDROPP4

Flexibility meets design! Professionals and rental firms are better prepared with this uplight! Whether they're standing, hanging or mounted in some other way, our DROP series uplights always look good. This is thanks to their intelligently attached bracket with no visible screws. The innovative bracket is screwed onto the uplight from below and not from the side as is standard. This means that when unmounted, the lamp boasts a very clean, simple exterior. Mounting options are flexible, either on the bracket or standing on rubber feet. When positioned upright and standing (without the mounted bracket), a built-in adjustment screw is available for tilt manipulation. Rated with protection class IP65, this uplight is also suitable for outdoor use.

Technical Informations

Product type

LED Wash Light

Type

Outdoor PAR

Colour spectrum

RGBWA + UV

**Number of LEDs**

4

LED type

15 W

Dispersion

22 °, 32 °, 40 °

DMX input

XLR 3-pin female

DMX output

XLR 3-Pol male IP65

DMX Functions

Colour change, colour fade, colour macro, Colour temperature correction, Dimmer, Dimmer Curve, Dimmer Fine, Dimmer response, LED PWM Frequency, RGBWA + UV, RGBWA + UV Fine, strobe

Standalone modes

Auto programs, colour macro, Colour Mix, Master / Slave mode, strobe, Tunable White, User Colours

Control

DMX, RDM

Controls

Down, Enter, Mode, Up

**Indicators**

OLED Display

Power consumption

45 W

Power connector

Neutrik PowerCON TRUE1 IN / OUT

Housing material

ABS, Metal

Cabinet colour

Black

IP class

IP65

Cooling

Silent, temperature controlled fan

Luminous flux

1400 lm

**Maximum Ambient
Temperature**

0 – 40 °C

Relative Humidity

< 85 %, not condensing



Certification

E, ETL, FCC, RoHS

**Accessories
(included)**

1 x Mounting bracket, 2 x filter, Neutrik PowerCon

Dimensions

Width

186 mm

Height

170 mm

Depth

170 mm

Weight

3,1 kg