



HDBaseT to HDMI Receiver

xVision Converter Series



#XVVHDBT2HDMI

Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what might soon become your most trustworthy piece of equipment. Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on professional A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the xVision Video Converters.

Connections

Video Input

HDBaseT 1.0 on shielded EtherCON connector

Ethernet

Locking RJ45 EtherCON connector

Video Output

HDMI 1.4 with locking system



Supported Signals	Recommended cable	UTP CAT6a with EtherCON connectors *Contact Theatrixx Technologies for more info
	Video Format Support	HDMI 1.4
	HDCP Support	HDCP 1.4
	Ethernet Support	100 Mbps
Physical	Height	53 mm (2.08 in)
	Depth	180 mm (7.08 in)
	Width	107 mm (4.21 in)
	Weight	1 kg (2.2 lbs)
	Alternate Form Factor	Also available in Reversible Module
Environmental	Relative Humidity	0% to 90% non-condensing



**Operating
Temperature**

0-40 °C

Power Requirements

Power Supply

Built-in power supply
PowerCON input
Edison Nema 5-15 output (loop-thru)

Power Consumption

15W

Voltage Range

100-120V, 50-60Hz
(100-240V, 50-60Hz available with PowerCON True1)

Courtesy Outlet

Max 10A, same voltage as input

In the box

xVision Converter HDBaseT to HDMI

AC Mains to PowerCON cable (1.5m, specify plug type
at ordering)

Certifications



DESIGNED & MANUFACTURED
IN CANADA

