



SDI Distribution Amplifier 1:4 - True1

xVision Converter Series



#XVVSDIDAT1

Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what might soon become your most trustworthy piece of **equipment**. Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on professional A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the xVision Video Converters

Connections

Video Input

1 x 3G/HD/SD SDI BNC

Video Output

4 x 3G/HD/SD SDI BNC
(reclocked and amplified)

Supported Signals

3G Format Support

1080p50, 1080p59.94, 1080p60.



HD Format Support

720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30

SD Format Support

525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL

SDI Video Sampling

4:2:2 and 4:4:4

SDI Audio Sampling

Sample rate of 48 kHz and 24 bit

SDI Color Space

YUV and RGB

SDI Auto Switching

Automatically detects incoming signal format

SMPTE Standards

425M Level A & B, 424M, 292M, 259M

Physical

Height

50 mm (1.97 in)

Depth

180 mm (7.08 in)

Width



107 mm (4.21 in)

Weight

1 kg (2.2 lbs)

Alternate Form Factor

Also available as a Reversible Module

Environmental

Relative Humidity

0% to 90% non-condensing

Operating Temperature

0-40 °C

Power Requirements

Power Supply

Built-in power supply
PowerCON True1 input
PowerCON True1 output (loop-thru)

Power Consumption

15W

Voltage Range

100-240V, 50-60Hz
(100-120V, 50-60Hz available with PowerCON /Edison Nema 5-15)

Courtesy Outlet

Max 10A, same voltage as input

In the box

xVision Converter SDI Distribution Amplifier 1:4 True1
AC Mains to PowerCON True1 cable (1.5m, specify



plug type at ordering)

Certifications



DESIGNED & MANUFACTURED
IN CANADA 

