



# Mega-Coupler

The Light Source



## #MLB / MLM

The Mega-Coupler has a 1/2" x 1 1/4" Hex Head Bolt with The Light Source Wing Nut. Our Mega-Coupler has solid nut tabs that won't break off. It uses standard 1/2 inch by 1-1/4 inch long hex head grade 8 bolts to secure your load. The bolt head locks into the hex milled pocket so that you can tighten the nyloc nut while the clamp is installed. The Mega-Coupler fastens from (1-1/4" Pipe) 1.66" OD to 2" OD truss tube and has the industry compatible 14 mm thick base.

### Options

1/2" x 1 1/4" Hex Head Bolt with Nylock Nut (Standard Mega-Coupler).  
1/2" countersunk (CS) flat head bolt.  
3/8" countersunk (CS) flat head bolt.  
3/8" x 1" Hex Head Bolt (3/8).  
1/2" x 1 1/4" stainless steel (SS) bolt.  
1/2" x 1 1/4" steel wingnut (SW).  
\*Contact us for models available in stock

### Minimum Size

1.25" pipe, 1.66" OD pipe

### Maximum Size



1.5" pipe, 1.90" OD pipe, 2" OD truss tube

**Working Load Limit**

1,100lb 500kg

**Standard hardware**

1/2-13 x 1 1/4" Hex Head grade 8 zinc plated steel bolt  
with nylock nut  
1" Belleville Washer

**Weight**

1.2 Pounds

**Finish**

Black (MLB)  
Alu (MLM)