



Totem 2.5mm

Totem Series



#XVA-2.5S-IN

Every detail of the Theatrix Totem has been designed to ensure maximal impact and delivery of your message in a clear and appealing way. The Theatrix Totem is a standalone, fully autonomous digital signage display. It can be used either as a free-standing structure (with optional locking casters) or as a digital power installed to a wall or suspended from the ceiling in any orientation. Its direct-view LED display ensures readability even in bright environments, and a strong plexiglass cover protects its surface against long term damage. Each Totem can be connected to WiFi and loaded with new content with just a few clicks. A user-friendly PC application allows the management of your fleet of Totems on a local network, and creating new slides is as easy as designing a PowerPoint slide show. The software also provides detailed logging such as play counts, easily exportable to Excel. Totems can even be controlled from iOS or Android devices, and an optional, subscription-based cloud platform allows the handling of a larger fleet of device from anywhere in the world.

Pixel

Packaging

RGB SMD 3-in1 LED

Pixel Pitch

2.571 mm

Mechanical

Cabinet resolution



224 x 756 px

Cabinet dimensions

596 x 1964 mm

Cabinet weight

36 kg

Cabinet thickness

39 mm (excl. control box and base)

Module resolution

112 x 84 px

Module dimensions

288 x 216 mm

Installation

Wall mount, floor stand

Cooling

Passive

Optical

Brightness

>800 nits

Lifespan

50 000 hours



	Color Temp.	6 500K
	Horizontal Viewing Angle	160°
	Vertical Viewing Angle	160°
Processing	Driving Mode	TBC
	Grayscale depth	TBC
	Refresh Rate	Up to 4 000 Hz
	Video Frame Rate	60 Hz
	Control System	Novastar T6
Environmental	Protection Rating	IP40
	Operating Temp.	-10°C @ 50°C



	Relative Humidity	10-90% RH
	Warranty	2 years
Power Requirements	Max. Power Consumption	600W/unit
	Average Power Consumption	210W/unit
	Input Voltage	100-240V, 50-60Hz auto-ranging
