



# VX4S-N

NovaStar



## #VX4S-N

The VX4S-N is a professional LED display controller. Besides the function of display control, it also features in powerful front end processing, so an external scaler is no longer needed. VX4S-N, with integrated professional interfaces and with excellent image quality and flexible image control, greatly meets the needs of the broadcast industry. It's a user-friendly interface that makes working with the display has never been as easy and as enjoyable than with VX4S-N.

### Input Power

AC100?240VAC?50/60Hz

### Overall Power Consumption

25W

### Operating Temperature

-20~60°C

### Size



482.6x251.5x45?mm?

**Weight**

2.55 Kg

**Input Index**

**2x CVBS**

PAL/NTSC

**2x VGA**

VESA Standard, support max. 1920x1200@60Hz input

**1x DVI**

VESA Standard (support 1080i input), support HDCP

**1x SDI**

480i, 576i, 720P, 1080i/P

**1x HDMI**

EIA/CEA-861 standard, in accordance with HDMI-1.3 standard, support HDCP

**1x DP**

VESA Standard

**Output Index**

**1x DVI LOOP**

Consistent with DVI input

**1x VGA**

Monitoring output connector  
Up to 1920x1200@60Hz output resolution



**1x DVI**

Monitoring output connector  
Up to 1920x1200@60Hz output resolution

**1x SDI LOOP**

Consistent with SDI input

**4x LED OUT**

4 Gigabit Ethernet outputs. Only Ethernet port 1 supports audio output. When the multifunction card is connected for audio decoding, the multifunction card must be connected to the Ethernet port 1.

---

Certifications

