



#SD112A

Built to withstand the daily hazards of touring, the SD-112A Theatrixx electrical Distribution is made to minimize the technical back stage area by taking only 6 rackmount units. The front panel is cut from a thick 3/16" aluminum sheet and is fixed to a robust steel chassis with rear support. All circuit breakers can be installed recessed with the addition of acrylic spacers for protection (optional). This type of power distribution is designed for audio, lighting and stage power applications. It offers 4 separate P&S 30A 120/208V 3 phases (C5) connectors over a 100A 3 phases Main Breaker. Panel mount terminals and neon indicators allow quick and easy voltage checks.

Input Connector CAM In/Thru – Straight or Ground/Neutral Reversed Breaker 100A 120/208V 3 phases Main Breaker Outputs Connectors

| | Breakers | 4x 30A 120/208V Circuits |
|----------------|--|---|
| Features | Phase Presence Indicators | 1x neon light per input phase |
| | Voltage Metering Jacks | 1x fused tip jack per input phase + 1x unfused tip jack on Neutral |
| | Enclosure construction | Robust steel housing |
| Dimensions | Height | 266.70 mm (10.50?) – 6RU |
| | Depth | 538.00 mm (21.18?) |
| | Width | 482.60 mm (19.00?) |
| Certifications | DESIGNED & MANUFACTURED IN CANADA 🍁 | |