Reversible Module

SDI Audio De-Embedder

XVVRMSDI2AUDIO

SDI —

(S) sound





The SDI Audio De-Embedder Reversible Module fits in the 8-Bay Reversible Rackmount Converter system.

theatrixx

The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

Specifications

_		•
$I \cap D$	$n \wedge c \cdot 1$	tions
CUII	HECH	LIUIIS

1 x 3G/HD/SD SDI BNC Video Input Loop-thru 1 x 3G/HD/SD SDI BNC

Video Output 1 x HDMI 1.2 type A with locking system

2 x Balanced + 4dB XLR (analog) each with a **Audio Ouput**

3-segment LED meter

Supported Signals

3G Format Support 1080p50, 1080p59.94, 1080p60

HD Format Support 720p50, 720p59.94, 720p60, 1080i50,

1080i59.94, 1080i60, 1080p23.98,

1080PsF23.98, 1080p24, 1080PsF24, 1080p25,

1080PsF25, 1080p29.97, 1080PsF29.97,

1080p30, 1080PsF30

525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL **SD Format Support**

4:2:2 and 4:4:4 **SDI Video Sampling**

SDI Audio Sampling Sample rate of 48 kHz and 24 bit

SDI Color Space YUV and RGB

SDI Auto Switching Automatically detects incoming signal format

De-Embedding SDI Channels 1 & 2

SMPTE Standards 425 M Level A & B, 424 M Level A, 292 M, 259 M

Physical Specifications

Height 121.5 mm (4.78 in) Depth 225 mm (8.85 in) Width 41 mm (1.61 in)

Weight 710 g (1.56 lbs)

Alternate Form Factor Also available as a standalone converter

Environmental Specifications

Relative Humidity 0% to 90% non-condensing

Operating Temperature 0-40 °C

Power Requirements

Reversible redundant power fed by XVVRF8 **Power Supply**

(8-Bay Rackmount Frame)

Power Consumption 20W

12VDC Voltage Range

In the Box

Theatrixx Reversible Module SDI Audio De-Embedder

Certifications & Compliance

This device complies with the following international standards



Ordering Information

XVVRMSDI2AUDIO Theatrixx Reversible Module SDI Audio De-Embedder

XVVRF8 Theatrixx 8-Bay Reversible Frame

XVVRMBLANK Theatrixx Blank Module