

# The Light Source

## Coupler with Eye Nut



The Mega-Coupler with Eye Nut has a Forged Steel Eye Nut for making rigging connections from a pipe or truss. The Forged Eye Nut is secured to the Mega-Coupler with a 1/2" flathead socket screw with permanent loctite. The Eye Nut rigging connection is 2-3/4" below the pipe and is able to swivel for proper orientation before loading. The Mega-Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Mega-Coupler has our wide wing nut for fastening the clamp to the pipe or tube. Safe Vertical Working Load 1100 Pounds, (500 KG).

|                           |   |
|---------------------------|---|
| <b>Minimum Size</b>       | 1.25" pipe, 1.66" OD pipe   |
| <b>Maximum Size</b>       | 1.5" pipe, 1.90" OD pipe, 2" OD truss tube  |
| <b>Working Load Limit</b> | 1100 Pounds   |
| <b>Hardware</b>           | Forged steel eye nut.<br>1/2" flathead socket screw with permanent loctite.   |
| <b>Dimensions</b>         | 2.5" Tall 2" Wide .4" Thick I.D. of 1.2" Wide I.D. of 1.5" Tall The I.D. is pear shaped   |
| <b>Weight</b>             | 1.3 Pounds  |
| <b>Case Quantities</b>    | 24  |
| <b>Order Codes</b>        | <b>MLMSE</b> Mega-Coupler with Eye Nut, Silver<br><b>MLBSE</b> Mega-Coupler with Eye Nut, Black Anodized<br><b>MLMSE-SW</b> Mega-Coupler with Eye Nut, Steel Wing Nut, Silver<br><b>MLBSE-SW</b> Mega-Coupler with Eye Nut, Steel Wing Nut, Black Anodized<br><b>MLWSE</b> Mega-Coupler with Eye Nut, White Powder Coat |