



49" Professional UHD Signage Displays

Key Features



Scheduler

The built in scheduler is one of the many important included features. The scheduler allows you to plan daily routines of when the display is powered on or off, along with selection of different sources or USB playlists.



Auto Launch

We have made it easy to give any HTML5-based application link to the display within the SoC software. Upon this, the display will start with the given link. The application can either be an offline or an online application, allowing the customers to execute their own application.




Built-in Connectivity

This series features wired and wireless connectivity such as embedded WiFi and Bluetooth. Due to the wireless capabilities, the displays can easily gather its content without any external device. Moreover, WiFi allows screen sharing to be enjoyed with Miracast.



USB Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



Display Control

Digital Signage Display SoC enables the users to control our displays using RS232 commands in a Local Area Network. Together with the full RS232 command list you can change/set volume, turn on/off the monitor, set a schedule for content display, set a webpage link to be displayed and give a wide range of commands in real-time.

PANEL

Screen Size	49"
Panel Technology	IPS
Backlight Type	Direct-Type LED
Brightness (typical)	500 cd/m ²
Native Resolution	3840 x 2160 (16:9) - UHD
Contrast Ratio (typical)	1200:1
Dynamic Contrast Ratio	50000:1
Response Time (typical)	8 ms
Active Area (H x V)	1074 x 605 mm
Pixel Pitch (H x V)	0.5593 x 0.5593 mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	8bit, 16.7 M colors
Screen Treatment	3H
Haze Level	1%
Refresh Rate	60 Hz
Orientation	Landscape / Portrait
Operation Hours	24/7
Area of Usage	Indoor

MONITOR CONNECTIVITY

RGB Input	VGA(DE-15F)
RGB Output	N/A
Video Input	4xHDMI2.0,1xDP1.2a, 2xUSB2.0, USB2.0(Internal)
Video Output	HDMI2.0, DP1.2a
Audio Input	Line In L/R
Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)
External Sensor	RJ12

ENVIRONMENTAL CONDITIONS

Operating Temperature	0-40°C
Operating Humidity	10-90%

POWER CONSUMPTION

Typical	83W (TBD)
Deep Standby	≤0.5 W

ACCESSORY

Standard	QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable
----------	--

MAINBOARD

Mainboard Model	17MB135VS
-----------------	-----------

MECHANICAL

Product Dimensions (WxDxH)	1102 x 104 x 635 mm
Package Dimensions (WxDxH)	1215 x 165 x 775 mm
Product Weight	13.7 kg
Package Weight	17 kg
Vesa Mounting	200 x 200 mm - M6
Bezel Width	" B:11 T:8 L/R:8 mm"

POWER

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

FEATURES

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock
Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance, IR Overlay Touch Compliance
Speaker	2 x 8 W

CERTIFICATION

Safety	YES
EMC	YES
CE	YES